

HBO Microlithography Lamps for ASML i-line Systems



Areas of application

- Microlithography

Product features and benefits

- High spectral intensity with peak irradiance at 365nm wavelength, making it ideal for microlithography
- Designed for long lasting performance
- Qualified with ASML
- Qualified with ASML



Product family datasheet

Technical data

	General Product Information			
Product description	Product number (Americas)	Product name (Americas)	Family brand	Global order reference
HBO 1003 W/PIL	69180	HBO 1003 W/PIL	НВО	HBO 1003 W/PIL
HBO 1500 W/PIL	69181	HBO 1500W/PIL 6/CS 1/SKU	НВО	HBO 1500 W/PIL
HBO 2100 W/PIL	69501	HBO 2100W/PIL 1/CS 1/SKU	НВО	HBO 2100 W/PIL
HBO 2500 W/PIL	69172	HBO 2500W/PIL 1/CS 1/SKU	НВО	HBO 2500 W/PIL
HBO 3500 W/PIL	69117	HBO 3500W/PIL 4/CS 1/SKU		HBO 3500 W/PIL

		Electrical Data		Photometri c Data
Product description	Lamp type	Nominal wattage	Nominal voltage	Light center length (LCL)
HBO 1003 W/PIL		1003 W	27.1 V	85.0 mm ¹⁾
HBO 1500 W/PIL	DOUBLE ENDED	1500 W	23 V	118.0 mm 1)
HBO 2100 W/PIL		2100 W	24 V	118.0 mm 1)
HBO 2500 W/PIL	DOUBLE ENDED	2500 W	28.0 V	149.0 mm
HBO 3500 W/PIL		3500 W	23 V	154.0 mm

	Physical Attributes & Dimensions	Operating Conditions		Lifetime Data
Product description	Length	Burning position	Cooling	Nominal lifetime
HBO 1003 W/PIL	195.0 mm	Other ²⁾	Forced ³⁾	1500 hr
HBO 1500 W/PIL	273.0 mm	Other ²⁾	Forced ³⁾	1500 hr
HBO 2100 W/PIL	240.0 mm	Other ²⁾		1500 hr
HBO 2500 W/PIL	340.0 mm	Other ⁴⁾	Forced ³⁾	1500 hr
HBO 3500 W/PIL	360.0 mm	Other ⁴⁾	Forced ³⁾	

	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Product description	Primary article identifier	Declaration no. in SCIP database	Candidate list substance 1	CAS No. of substance 1
HBO 1003 W/PIL	4050300461380 4050300967097	b9c92b80-c1d8- 4748-8fda- 1d2d66728131 31a5877e-d4ec- 4106-b4a4- a38a88565ee5	Lead	7439-92-1

Product family datasheet

Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) Product description Primary article Declaration no. in **Candidate list** CAS No. of substance identifier SCIP database substance 1 1 HBO 1500 W/PIL 4050300967103 | 910a2e30-b741-Lead 7439-92-1 4050300461465 4571-8470-190c5ee7888d | e22d7304-fdce-45fd-8d2a-6aa5291d1a5b HBO 2100 W/PIL 4050300800431 e65b3165-1b6a-7439-92-1 Lead 4da8-9fd8-852bef40597d HBO 2500 W/PIL 4050300947396 7439-92-1 7eee76a5-c4d5-4b9f-Lead b456-ddffe12f4ebb HBO 3500 W/PIL 4008321355843 34bb99bc-0897-Lead 7439-92-1 4e24-883a-0817db1e7cd5

Product description	Safe use instruction
HBO 1003 W/PIL	The identification of
	the Candidate List
	substance is
	sufficient to allow
	safe use of the
	article.
HBO 1500 W/PIL	The identification of
	the Candidate List
	substance is
	sufficient to allow
	safe use of the
	article.
HBO 2100 W/PIL	The identification of
	the Candidate List
	substance is
	sufficient to allow
	safe use of the
	article.
HBO 2500 W/PIL	The identification of
	the Candidate List
	substance is
	sufficient to allow
	safe use of the
	article.
HBO 3500 W/PIL	The identification of
	the Candidate List
	substance is
	sufficient to allow
	safe use of the
	article.

¹⁾ Distance from end of base to tip of anode or cathode (cold)

²⁾ Anode underneath

³⁾ Maximum permissible base temperature: 200 °C

⁴⁾ Anode on top

Product family datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.