### Product family datasheet

# LEDriving SL P21W RED

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Red



Easy upgrade to LED technology with plug & play solutions

**Replaces conventional P21W lamps** 



Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



#### Suitable LED replacement for P21W

LEDriving SL P21W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

# Product family datasheet

# Technical data

|                            | Product informa                                | tion   | General Product |                                  | Electrical Data |                                     |                |
|----------------------------|--|--|-----------------|----------------------------------|-----------------|-------------------------------------|----------------|
| Product description        | Application (Cat<br>and Product spe            |  | Global o        | Global order<br>reference        |                 | Nominal voltage                     |                |
| LEDriving SL ≜ P21W        | Mainly used for signal/ indicator applications | Off-road ≙<br>P21W   | 7506DRI         | p                                | 1.8 W           | 12 V                                |                |
|                            |  |  |                 | Photometric Data                 |                 | Physical Attributes &<br>Dimensions |                |
| Product description        | Nominal wattag                                 | e Power<br>input<br>toleranc<br>e  | Test<br>voltage | Nominal luminous<br>flux         |                 | Lamp base                           | 9              |
| LEDriving SL $\doteq$ P21W | 1 W  | ±25 %  | 13.5 V          | 100 lm                           |                 | BA15s                               |                |
|                            |  |  |                 |                                  |                 | Lifetime D                          | ata            |
| Product description        | Length   | Diameter   |                 | Diameter                         |                 | Lifespan<br>B3                      | Lifespan<br>Tc |
| LEDriving SL $\doteq$ P21W | 52.5 mm  | 25.0 mm  |                 | 25.0 mm                          |                 | 1500 hr                             | 4000 hr        |
|                            |  | Environmental & Regulatory Information<br>Information according Art. 33 of EU Regulation (EC) 1907/2006<br>(REACh) |                 |                                  |                 |                                     |                |
| Product description        |  | Primary article<br>identifier  |                 | Candidate list CAS substance 1 1 |                 | lo. of substance                    |                |
| LEDriving SL $\doteq$ P21W |  | 4062172401371 <br>4062172152204  | Lead            | Lead 7439-92                     |                 | 92-1                                |                |

| Product description | Safe use instruction  | Declaration no. in<br>SCIP database          |
|---------------------|---|--|
| LEDriving SL ≜ P21W | The identification of<br>the Candidate List<br>substance is<br>sufficient to allow<br>safe use of the<br>article. | 5271a66b-2494-<br>48e0-aef0-<br>f73e7dcb0bfc |

 $^{1)}$  Light-emitting diode lamp

\_\_\_\_

# Product family datasheet

#### Download Data

| File  |
|---|
| User instruction<br>GPRS_Safety symbols instructions      |
| Brochures<br>LEDriving Retrofits - Exchange overview (EN) |

#### Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.