OSRAM

LEDguardian TRUCK FLARE Signal TA19

LEDguardian warning- and safety lights





Street legal in Germany

Carrying along in the vehicle and positioning of a warning light in the event of a brokendown vehicle is mandatory in Germany for all vehicles ≥ 3.5t in accordance with §53a TA19 StVZO



2 in 1

LED Warning Light & LED TorchlightBright yellow flashing light & Bright white torchlight



4x AA batteries included

Thanks to the included batteries, the warning light is ready for use immediately after purchase



2-year-OSRAM guarantee*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.



Light is safety-See and be seen with OSRAM

Be prepared - with OSRAM LEDguardian warning and safety lights.

The OSRAM LEDguardian TRUCK FLARE Signal TA19 is a LED warning light which must be carried along in the vehicle and used in the event of a break-down in Germany. This applies to all vehicles with a total weight of 3.5t according to §53a StVZO. In addition, the TRUCK FLARE from OSRAM also meets the requirements specified in the technical requirements of the StVZO (TA 19). These state that the warning light must fulfill the following characteristics: An orange flashing light, an uninterrupted operating time of at least 15h, a flashing frequency of 1.5 Hz

Product family datasheet

 \pm 0.5 Hz 90 \pm pulses per minute and a dynamic pressure 21 kg/m² wind force 9. Only those lights that meet these requirements are officially approved for use in road traffic. The warning light must be in operation next to the warning triangle to indicate the danger zone in the event of a breakdown or accident. For vehicles 3.5t the use is not mandatory, but for the safety of all road users of course possible and recommended.

The flashing orange warning light function of the OSRAM LEDguardian TRUCK FLARE Signal TA19 is visible from a great distance and can provide crucial information about a dangerous situation on the road in an emergency.

In addition to the warning triangle, it alerts other road users about a potentially dangerous situation on the road by actively flashing, compared to the simple reflection such as that of a warning triangle.

With 6 long-life high-power LEDs with up to 6000K, you can draw attention to yourself by day and night, and preventively alert and warn other road users of a dangerous situation, such as a broken-down vehicle on the road. In addition, the TRUCK FLARE can also serve as a torchlight. As an additional function, a bright white torchlight is integrated and enables additional applications such as a work or inspection light.

The compact design allows you to store the warning light within easy reach in the vehicle and, if required, it can be set up quickly and easily directly next to the warning triangle thanks to the fold-out, robust and non-slip feet. Another advantage is that the batteries included in the scope of delivery mean that the OSRAM LEDguardian TRUCK FLARE Signal TA19 is immediately ready for operation. The LEDguardian TRUCK FLARE Signal TA19 has been tested and validated in our DIN EN ISO/IEC 17025 certified environmental simulation laboratory for extreme external influences in terms of water, dust, heat, cold and impacts from falls. With an IP54 protection class, the OSRAM LEDguardian TRUCK FLARE Signal TA19 is resistant to the ingress of water and dust.

OSRAM provides a 2-year guarantee* on this product.

Product family datasheet

Technical data

| | Product information | General Product Information | | Electrical Data | | | |
|---------------------|---|--------------------------------|--|----------------------------------|---------|------------------|--|
| Product description | Application (Category and Product specific) | Global order reference | | Nominal volt | age | Nominal wattage | |
| LEDguardian TA19 | Warning and safety lights | LEDSL103 | | 6.0 V | | 3 W | |
| | Photometric Data | | Physica | Physical Attributes & Dimensions | | | |
| Product description | Color temperature | Light color LED | Height | | Widtl | h | |
| LEDguardian TA19 | 2000/6000 K | Orange / White | 236.0 mm 42.6 mm | | | | |
| | | | | Lifetime Data | Additio | onal product | |
| Product description | Length | Product weight | | Guarantee | Scope | of battery | |
| LEDguardian TA19 | 90.7 mm | 600.00 g | | 2 years | Yes | | |
| | | Capabilities | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | | |
| Product description | Type of Battery | Technology | Candidate list substance 1 | | CAS N | No. of substance | |
| LEDguardian TA19 | Alkaline | LED | Lead | | 7439 | -92-1 | |

| Product description | Safe use instruction | Declaration no. in SCIP database |
|---------------------|-----------------------|-------------------------------------|
| LEDguardian TA19 | The identification of | 22fd1329-c8ed- |
| | the Candidate List | 4629-9098- |
| | substance is | b8463fd1bea4 |
| | sufficient to allow | 712cce46-acd4- |
| | safe use of the | 400e-9e40- |
| | article. | af2a137be4de |
| | | 807bc44b-e1ed- |
| | | 4202-9d73- |
| | | 375218c16449 |

Product family datasheet

Download Data

| | File |
|----------|---|
| Z | User instruction LEDguardian TRUCK FLARE Signal TA19 |
| 太 | User instruction GPRS_Safety symbols instructions |
| 秀 | Brochures OSRAM LEDguardian Truckflare TA19 Flyer (EN) |
| D | Movie application Product Video OSRAM LEDguardian TRUCK FLARE Signal TA19 (EN) |
| D | Movie application Product Video OSRAM LEDguardian TRUCK FLARE Signal TA19 (EN) |
| D | Movie application LEDguardian ROAD FLARE Signal TA19 Social Media Reel (EN) |
| D | Movie application LEDguardian ROAD FLARE Signal TA19 Social Media Reel Camper (EN) |
| • | Video OSRAM LEDguardian TRUCK FLARE Signal TA19 - Camper |
| | ref_pim_amsp_product360degreeimages OSRAM LEDguardian Truckflare TA19 |

Legal advice

*for precise conditions please refer to:

www.osram.com/am-guaranteeApplication advice:

For more detailed application information and graphics please see product datasheet and user manual.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.