## **OSRAM**

# LEDriving SL T5

Ideal replacement for any vehicle



Suitable for various vehicle interior and exterior applications

Available in Cool White



Replaces conventional T5 lamps (e.g. ECE W2.3W)

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year guarantee (refer to www.osram.com/am-guarantee for precise conditions)



#### Suitable LED replacement for T5 (e.g W2.3W)

LEDriving SL T5 replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional T5 lamp bases (e.g. ECE W2.3W). In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

### Product family datasheet

#### Technical data

	Product information		General Product Information	Electrical	Data
Product description	Application (Category and Product specific)	Product type (off- road vs. on-road)	Global order reference	Power input	Nominal voltage
LEDriving SL ≜ W2.3W (T5)	Mainly used for signal/ indicator applications	Off-road ≙ W2.3W (T5)	2723DWP	0.25 W	12 V

				Photometric Data	Physical Attributes & Dimensions
Product description	Nominal wattage	Power input toleranc e	Test voltage	Nominal luminous flux	Lamp base
LEDriving SL	0 W	±20 %	13.5 V	25 lm	W2x4.6d

				Lifetime Data
Product description	Length	Diameter	Diameter	Lifespan Lifespan B3 Tc
LEDriving SL	16.5 mm	6 mm	6 mm	750 hr 2000 hr

	Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	Technology	Primary article identifier	Candidate list substance 1	CAS No. of substance
LEDriving SL	LED <sup>1)</sup>	4062172254687   4062172401838	Lead	7439-92-1

Product description	Safe use instruction	Declaration no. in SCIP database
LEDriving SL ≜ W2.3W (T5)	The identification of the Candidate List substance is sufficient to allow safe use of the	0c5665af-69f3-4cb5- 92d6-53765a15bdac   82245377-8731- 4a13-8ef4- 9051d2f6d948
	article.	

<sup>1)</sup> Light-emitting diode lamp

#### Product family datasheet

#### Download Data

#### File



User instruction
GPRS\_Safety symbols instructions



**Brochures** 

LEDriving Retrofits - Exchange overview (EN)

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.