Product family datasheet

OSRAM

BATTERYcharge PRO 100A





Developed by professionals - Made for professionals

The OSRAM BATTERYcharge PRO 100A is a professional, intelligent battery charger suitable for a wide range of battery types for 12V and 24V vehicles. Ideal for use when different vehicles and even entire fleets need to be maintained, especially in professional workshops or showrooms.

By selecting different battery types and charging levels, the user can set the specific charge required for the different battery types. The BATTERYcharge PRO 100A can deliver variable charging currents up to a maximum of 100A. This is possible for lead-acid batteries as well as lithium batteries and start/stop batteries. Variable charging rates can also provide flexible slow or fast charging to meet the individual requirements of each user. An integrated test function additionally enables diagnosis of the battery and alternator. OSRAM's professional battery charger with integrated LCD screen runs through a 7-stage charge cycle for lithium batteries and a 9-stage charge cycle for all other batteries to restore and optimize battery performance and improve charge retention. With its light weight, the professional charger from OSRAM is easy to carry and transport around the workshop.

Product family datasheet

Technical data

Product information	Electrical Data		
Application (Category and Product specific)	Charge Rate (Up to)	Maintainance Charge (up to)	Max battery capacity
Professional Battery Charger	100 A	100 A	1000 Ah
	Physical Attributes & [Dimensions	
Min battery capacity	Length	Width	Height
14 Ah	250.0 mm	350.0 mm	90.0 mm
Information according	Art. 33 of EU		
Candidate list substance 1	Declaration no. in SCIP database		
	No declarable		
	Application (Category and Product specific) Professional Battery Charger Min battery capacity 14 Ah Environmental & Regu Information according A Regulation (EC) 1907/2 Candidate list	Application (Category and Product specific) Charge Rate (Up to) and Product specific) Professional Battery Charger 100 A Physical Attributes & I Min battery capacity Length 14 Ah 250.0 mm Environmental & Regulation (EC) 1907/2006 (REACh) Candidate list Declaration no. in	Application (Category and Product specific) Charge Rate (Up to) Maintainance Charge (up to) Professional Battery Charger 100 A 100 A Professional Battery Charger 100 A 100 A Min battery capacity Physical Attributes & Dimensions Vidth 14 Ah 250.0 mm 350.0 mm Environmental & Regulation (EC) 1907/2006 (REACh) Vidth Vidth Candidate list Declaration no. in Vidth

Product family datasheet

Download Data

 File

 Image: Sector S

Legal advice

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.