

Данные о продуктовой линейке

LEDDriving HL EASY GEN 2 HB3/HIR1/H10/HB4/HIR2



Ultra compact LED replacement for conventional high and low beam lamps

“Socket Design” – no adapters and caps needed



Easy plug & play installation

Allowing a high compatibility and an easy installation



Cool White color temperature

Better visibility thanks to daylight effect



LED high and low beams lamps with plug & play system: no adapters and caps needed

With its socket-based solution, the OSRAM LEDDriving HL EASY GEN 2 retrofits provide an ultra-compact LED replacement of conventional high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility: no adapters and caps needed! An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation.

The LEDDriving HL EASY GEN 2 high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Данные о продуктовой линейке


Technical data

Описание продукта	Электрические параметры				Фотометрические данные
	Мощность на входе	Номинальное напряжение	Номинальная мощность	Тестовое напряжение	Световой поток
LEDiving HL EASY ≙ HB3/HIR1/H10/HB4/HIR2	26 W	12 V	26 W	13,2 V	2000 lm

Описание продукта	Допуск по отклонению светового потока	Физические характеристики и размеры	Срок службы	Нормативная и природоохранная информация Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
		Диаметр	Срок службы Тс	Основной идентификатор изделия	Номер декларации в базе данных SCIP
LEDiving HL EASY ≙ HB3/HIR1/H10/HB4/HIR2	±25 %	14.8 mm	1000 hr	4062172426428	В работе

Данные о продуктовой линейке

Загрузка данных

Файл	
	User instruction GPRS_Инструкции по символам безопасности

Рекомендации по применению

Для получения дополнительной информации и изображения продукции, пожалуйста, ознакомьтесь с инструкцией.

Примечание

В заказ могут быть внесены изменения без предварительного уведомления. Проверьте информацию на наличие ошибок. Убедитесь, что информация актуальна.

